



Division of Transportation

Paula J. Trigg, P.E.

Director of Transportation/County Engineer

600 West Winchester Road
Libertyville, Illinois 60048-1381
Phone 847 377 7400
Fax 847 984 5888

May 10, 2016

ADDENDUM #1
Buffalo Grove Road Patching
SECTION 16-00249-04-RS
Lake County Division of Transportation
Opening Time and Date:
Tuesday, May 17, 2016; 10:00 a.m.

To all bidders:

Please remove the following pages of the Bid Package documents and replace them with the attached revised pages:

- Contract Specifications, Page 19 of 96
 - The special provision for PORTLAND CEMENT CONCRETE SURFACE REMOVAL 2” has been revised to include saw cutting.

Note that this revision does not result in any pay item or quantity changes.

Very truly yours,

A handwritten signature in black ink that reads "Michael G. Zemaitis".

Michael G. Zemaitis, P.E.
Engineer of Design

IDOT SPECIAL PAY ITEMS FOR ROAD AND BRIDGE CONSTRUCTION

Z0038121 PORTLAND CEMENT CONCRETE SURFACE REMOVAL 2"

Description: This work shall consist of removing the top 2" of existing concrete two feet either side of an existing pavement joint with a milling machine.

General: The work shall be performed according to Section 440 of the "Standard Specifications" and the following:

Prior to milling, the Contractor shall saw cut (2" depth) the perimeter of the patch with an approved concrete saw. A wheel saw may be used along the curb and gutter and at locations approved by the Engineer. This work will not be paid for separately but shall be included in the unit price of PORTLAND CEMENT CONCRETE SURFACE REMOVAL 2".

If the milling machine cuts too deep or tears out areas of the existing pavement which were not designated for removal, the holes shall be filled with leveling binder at the Contractor's expense.

The Contractor shall only mill patches to be resurfaced the same day. No milled areas shall be left open past the end of the allowable lane closure time.

Removed materials shall be disposed of outside the limits of the right-of-way according to Article 202.03 of the "Standard Specifications" and/or as directed by the Engineer.

Method of Measurement: Portland Cement Concrete Surface Removal will be measured for payment in place and the area computed in square yards.

Basis of Payment: This work will be paid for at the contract unit price per square yard for PORTLAND CEMENT CONCRETE SURFACE REMOVAL 2". *The unit price shall include all equipment, materials, and labor required to remove and dispose of the concrete surface.*